TITLE	DATE	REV
Product Requirements	9/18/2018	0

# TDRC Tubing Insulation Tooling for more Efficient and Ergonomic Insulation Installation on Hydraulic Tubing Sets

Team Name: BIG Authors: Richard Baptista Isaac Fisher Kaleb Halen Michael Odell

TITLE	DATE	REV
Product Requirements	9/18/2018	0

# **Document History**

Rev Number	Date	Modified By	Reason
0	9/18/18	Group	Initial Release

TITLE	DATE	REV
Product Requirements	9/18/2018	0

# Table of Contents

1 Objective	5
2 Scope	5
<b>3</b> References	5
3.1 Cited Documents	5
3.2 Acronyms	5
4 Functional Requirements	6
4.1 User Interface Requirements	6
4.2 What it should do	6
5 Mechanical Requirements	6
5.1 Strength Requirements	6
5.2 Spatial Requirements	6
5.3 Weight/Mass Requirements	6
5.4 Mounting / Interface Requirements	6
5.5 Appearance Requirements	7
5.6 Durability Requirements	7
5.7 Reliability Requirements	7
6 Electrical Requirements	7
6.1 Operational Voltage	7
6.2 Operational Power Capability	7
6.3 Energy Storage Capacity	7
7 Software Requirements	7
7.1 Functionality	7
7.2 User Interface	7
8 Environmental Requirements	8
8.1 Temperature	8
8.2 Environmental Sealing	8
9 Regulatory Requirements	8
9.1 UL REQUIREMENTS	8
9.2 Shipping Requirements	8
10 Cost Requirements	8
10.1 Prototype Cost	8

TITLE	DATE	REV
Product Requirements	9/18/2018	0

10.2 Production Requirements	8
11 Schedule Requirements	8

TITLE	DATE	REV
Product Requirements	9/18/2018	0

# 1 Objective

The objective of the Boeing Insulation-Installation Group (BIG) is to design and develop tooling or establish novel manufacturing techniques to improve the process of installing insulation on hydraulic tubing for Boeing commercial aircraft.

BIG is tasked with the objective of improving the overall ergonomics and efficiency of the manufacturing process currently orchestrated by the Boeing Tubing Ducting and Reservoir Center (TDRC). It is necessary for the tubing installation to be defect-free, consistent, user-friendly and reduce current manufacturing times. The proposed method/tooling developed by BIG must be reviewed by an engineering team at TDRC.

# 2 Scope

Propose a defect free solution to reduce assembly time and eliminate ergonometric exposure.

# 3 Functional Requirements

#### 3.1 User Interface Requirements

The device should be a user friendly mechanism that simplifies the installation process and increases productivity. Ideally the device should be able to meet the following requirements:

- Device shall insulate a tube in under three minutes
- Device shall be multipurpose and be compatible with various bends
- Device shall be compatible with tubes of various lengths
- Device shall reduce input from user
- Device shall maintain a consistent and uniform appearance
- Device shall appropriately set insulation within tolerances for end conditions
- Device shall be compatible with tube diameters ranging from:
  - o <sup>3</sup>/8"
  - $^{\circ}$   $\frac{1}{2}$ "
  - o <sup>5</sup>/8"
  - o <sup>3</sup>/<sub>4</sub>"
  - 0 7/8"
  - o 1"
- Device shall not permanently warp tubing
- Device shall not destroy insulation

TITLE	DATE	REV
Product Requirements	9/18/2018	0

#### 3.2 What it should do

Insulate tubing without damage to the insulation or the tube. Reduce assembly time and eliminate ergonometric issues

### 4 Mechanical Requirements

#### 4.1 Spatial Requirements

This device should be user driven, staying in the constraints of the current working area.

#### 4.2 Durability Requirements

The mechanism should be able to handle 50-100 a day, easily keeping up with the 5000 items a year.

#### 4.3 Reliability Requirements

All components shall have 95% reliability

# **5** Electrical Requirements

#### 5.1 Operational Voltage

The system should be able to operate off a standard 120V wall outlet, or air.

### **6** Software Requirements

#### 6.1 Possible

Possible use of an Arduino to control the prototype.

TITLE	DATE	REV
Product Requirements	9/18/2018	0

# 7 Environmental Requirements

#### 7.1 N/A

This project will be designed to operate in a controlled, indoor, and air conditioned environment.

### 8 Cost Requirements

#### 8.1 Prototype Cost

Cost of the first prototype shall not exceed \$500.

#### 8.2 Production Requirements

Projected cost for production units shall be < \$1500.

# 9 Schedule Requirements

The following are the major Project Milestones:

-	Approval of Requirements	Sept.	30,	2018
		3.7	20	0010

- Concept Design Review Nov. 30, 2018
  Detailed Design Review Feb. 9, 2019
- Detailed Design Review
   ER of drawing package
   Feb. 9, 2019
   March 2, 2019
- EK of drawing package March
- Complete Prototype build April 5, 2019
- UI Design EXPO April 26, 2019
- Final Report / Drawings May 4, 2019