Senior Capstone Design

Project: USDA - Stream Velocity

Primary Author: Max Rietze

Team: Stream Team

Date: 4/29/2021

Design Validation Plan & Results (DVP&R)

| Requirement | Test | Test Subject | Target Date | Result | Recommendation |
|--|---|--|-------------|---|---|
| Probes communicate 100ft away | separate probes by 100ft and test for communication | HC 12 wireless transmitter | 10/28/20 | Successful Test the probes comunicated | |
| Probes communicate 100ft away with interferance | separate probes by 100ft and test for communication with pipe wall inbetween | HC 12 wireless transmitter | 10/28/20 | Material interferance didnt seem to be an issue with communication | |
| Probes communicate 100ft away | separate probes by 100ft and test for communication | HM 10 (bluetooth) wireless transmitter | 11/4/20 | Successful Test the probes comunicated | |
| Probes communicate 100ft away with interferance | separate probes by 100ft and test for communication with pipe wall inbetween | HM 10 (bluetooth) wireless transmitter | 11/4/20 | Material interferance didnt seem to be an issue with communication | |
| Pipe is water proof when caps are on. | pour water over tube and ends then dry off and check for internal moisture | Probe container | 4/17/21 | Water was able to seep through the threading on the 3D printed cap | Add an O-ring to not let the water into the housing |
| circuit casing is water proof | pour water into the outter tube and make sure no water enters the secondary container | inner circuit container and outter pipe | 2/17/21 | N/A. We removed the secondary container from the design | |
| batter life is at least 10hrs in duration | run the system with a timer and periodically check if it has died up to 10 hrs | battery pack | 2/17/21 | The probes were able to send data continuously overnight with no problems | |
| the outter pipe must be durable | apply force to outter tube and check for cracking or substantial damage | device handle and container | 11/11/20 | The PVC should be able to with stand the stresses that it will be put under | |
| system is capable of transitioning to small stream form | the probe is easily detachable from main handle and easily attachable small stream flag | probe and clips | 2/17/21 | The extendable handle is removable, which makes for an easy transition to small streams | |
| data is accurate and reads with a high enough resolution | run old system and new system to compare data | probes | 11/11/20 | The data ligned up with the old systems and was reading accurately | |
| probes read simultaionly | insert probes into water and have them communicate their data at the same time | probes and circuit | 10/28/20 | The probes output simultaioniously | |
| Retractable wire | try to retract wire with reel system | reel system | 4/26/2021 | Wire tangled, not succesful | Try draging the wire vs. winding it up |