

Seed Storage

Team Seed Squad

University of Idaho College of Engineering

Solution/Final Design

- The seal between the bag and valve system is quick

and easy to put together without wrinkling the bag

- The total cost is around \$80 depending on the

- The bag can be easily opened and closed from one

by the Idaho Bean Commission

Problem

In developing countries, farmers do not have access to decent seed storage facilities. When farmers try to store their supply of seed, insects and wet climates

often degrade or destroy it.

Project Goal

Design, fabricate, and test a capsule that will keep seed dry, protect against insects, be easy to assemble and

Goal	Target
Keep seed dry	Less than 12% humidity
Store deed for long periods of time	Minimum of 2 years
Cheap	At most \$250
Easy to assemble	Less than 1 hour
Transported by hand	Less than 200 pounds
Vacuum	Hold at -20 inHg for 3 days
Loading and unloading time	Less than 10 minutes
Storage volume	At least 4.7 cubic feet



Joel Wilson, David Smith, Joshua Begay, Peter Handel

Project Learning

Design 1: PVC pipe and fittings are too expensive

- Total cost for 12 inch pipe is \$1500


Design 2: Barrel structural integrity and Final Design leak rate


- Barrel deforms too much
- Supports would need to be very strong
- Unsuccessful airtight seal on barrel Design 3: Trash bag seal around PVC

Designocouldn't hold the pressure

tube

- Melting the bag together was





Leak rate too high



Leak Rate

Meet all design goals


Design 3

- Experiments we conduct

quality of parts

- The leak rate is 0.026 in Hg/hour

end



Vacuum Bag Leak Rate

