

## Project Objective

- Design and fabricate the experiment equipment to measure the temperature gradient through several types of insulation.
- Record the temperature decay over time for different insulation materials by using the designed testing equipment.

### Requirements

## Testing Equipment Characteristics Design Considerations:


- Testing equipment easily transported through doors.
- Interchangeable building insulation materials.
- Durable Test Equipment.

### **Experiment**

- Test duration of 90 minutes,
- Testing specimens of equal thickness,
- Accuracy: +/- 1 Degree F,
- Data sampling frequency of 1 sample/s.

### Design of Testing Apparatus





#### <u>Sensors</u>







# Insulation Testing

Yue Yu, Nick Chen, Cameron Moore, Austin Anderson


## Experimental Setup





- Boxcar 4.3 data acquisition system integrated the laptop with the temperature sensors.
- Test equipment interchangeable for different insulations.
- Heat source within the box.
- HOBO sensors for recording temperatures from the interior and exterior surfaces, as well as interior and exterior air temperatures.

## Testing Materials






Aerogel, Cameron's Carpet, R\_max Thermosheath


### **Project Conclusions**

- Figure 1 depicts a comparison of the temperature profiles over time for aerogel and R\_max.
- Figure 2 illustrates a comparison of temperature decay over time for various insulation types. The upper curve indicates a more effective insulation.
- Figure 3 demonstrates comparison of the temperature decay rate for the different insulations. The lower slope indicates a more effective insulation.



### Results





### Acknowledgements

- Dr. Rezaie, Supervisor
- Scott Smith

Figure 2

- Dave Hamilton
- UI Facilities
- Dr. Beyerlein